

DERMAFLEX SE30

DERMAFLEX SE 30 is an acrylic polymer.

TYPICAL ANALYSIS

Appearance	viscous limpid liquid
Solids content	$30 \pm 2 \%$
pH (10 % solution)	6.5 ± 1.0
Stability to acids	Stable
Stability to electrolytes	Very good
Lightfastness	Very good

PROPERTIES

DERMAFLEX SE 30 is an acrylic polymer which gives the leather good firmness though maintaining a soft and mellow hand.

It can be used both in acidic and in neutral conditions without problems.

It is especially suitable to minimize the problems of blowing of the grain on empty parts of leather ensuring a particularly fine patent.

Having good lightfastness, it may be used also for light shades and production of white crust.

APPLICATION

DERMAFLEX SE 30 is used in retanning with mineral tanning agents or after neutralization, from 3.0 to 6.0 %, depending on the particular requirements.

When correctly stored, it is stable 12 months.

This sheet is a synthetic illustration of the product to enable the user to employ it at the best.

Properties and values are not, therefore, sales specifications.

Taking into account the several possibilities of application of this product, no warranty of the results is possible.

Expiry date refers to the product well closed in the original container, in fresh and dry area. Some particularly sensitive products, when open, should be used rapidly.

Stir well before using the product, close tightly the container to preserve the properties.

Our technical service is at your disposal for any recommendation.

MOD 043 rev 1 Edition n. 2



DERMACOLOR s.r.l.
ph. +39 0571 47.13.13
e-mail info@dermacolor.it