

MICROLAC CP-3

Chemical nature	Nitrocellulose varnish
Appearance	Viscous liquid
Solids content	23.0 ± 2.0 %

Applicazioni

MICROLAC CP-3 è una lacca in solvente molto plastificata che forma un film liscio con tatto naturale e buon riempimento. Essa è adatta per impieghi generali come lucido fissativo finale. È dotata di buone proprietà di solidità allo sfregamento a secco e ad umido. Può anche essere usata, da sola o in combinazione, per ottenere il grado di lucido desiderato. È preferibile diluire il prodotto (1:3) prima dell'uso.

Main applications

MICROLAC CP-3 is a solvent lacquer highly plasticized which forms a smooth film with natural touch and good filling. It is suitable for general purposes as gloss final fixing agent. Very good properties of rubbing, both wet and dry. May be used alone or in combination to obtain the desired degree of gloss. Best to dilute the product (1:3) before using.

KEEP FROM FREEZING - CAN BE STORED FOR 6 MONTHS BETWEEN +5 AND +35°C

This sheet is a synthetic illustration of the product to enable the user to employ it at the best. Properties and values are not, therefore, sales specifications. Our application recommendation are in line with our present state of knowledge and they do not exempt the customer from performing his own tests to determine the suitability of the supplied products for the intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere or responsibility. **Expiry date refers to the product well closed in the original container, correctly stored. Some particularly sensitive products, when open, should be used rapidly. Stir well before using the product, close tightly the container to preserve the properties.** Our technical service is at your disposal for any recommendation.