

MICROPUR 1055

Chemical nature	Water dispersion of aliphatic polyurethane
Appearance	Liquid
Solids content	40.0 ± 2.0 %
pH	6.5 ± 1.0
Ionicity	Anionic

Applicazioni

MICROPUR 1055 è un poliuretano alifatico anionico in dispersione acquosa. Forma un film di elevata elasticità, ottima copertura, elevate resistenze alle flessometrie anche a basse temperature. È particolarmente indicato nelle rifiniture dove sono richieste alte performance di resistenza, come automotive .

Main applications

MICROPUR 1055 is water dispersion of aliphatic, anionic polyurethane and it forms very elastic films with excellent covering properties. It has very good resistance properties to flex and abrasion test. It's recommended for finishing which have to meet high fastness resistance such as automotive.

KEEP FROM FREEZING - CAN BE STORED FOR 6 MONTHS BETWEEN +5 AND +35°C

This sheet is a synthetic illustration of the product to enable the user to employ it at the best. Properties and values are not, therefore, sales specifications. Our application recommendation are in line with our present state of knowledge and they do not exempt the customer from performing his own tests to determine the suitability of the supplied products for the intended purposes. Application of the products lies outside the scope of our control and therefore comes within the customer's sphere or responsibility. **Expiry date refers to the product well closed in the original container, correctly stored. Some particularly sensitive products, when open, should be used rapidly. Stir well before using the product, close tightly the container to preserve the properties.** Our technical service is at your disposal for any recommendation.