

# DERMAFLEX CM

DERMAFLEX CM is a high molecular weight synthetic organic copolymer between styrene and maleic anhydride.

## TYPICAL ANALISYS

Solids	<i>approx 18 %</i>
pH (10 % solution)	$8.5 \pm 1.0$
Solubility	Miscible with water in all proportions

## PROPERTIES

DERMAFLEX CM is progressively less stable with decreasing pH values. Below pH 3.0 the copolymer will be completely precipitated with both minerals and organic acids.

DERMAFLEX CM solutions exhibit increasing instability in the presence of increasing concentrations of electrolytes and astringent chemicals. All these characteristics could be handled to create very special effects on the leathers treated.

The crust obtained applying DERMAFLEX CM is always soft and tight with a particular fine-patented grain.

## APPLICATION

From 2.0 to 6.0 % after or during neutralisation in all the articles.

From 2.0 to 4.0 % after fatliquoring as a grain-tightener.

When correctly stored, it is stable 12 months.

This sheet is a synthetic illustration of the product to enable the user to employ it at the best.

Properties and values are not, therefore, sales specifications.

Taking into account the several possibilities of application of this product, no warranty of the results is possible.

**Expiry date refers to the product well closed in the original container, in fresh and dry area.** Some particularly sensitive products, when open, should be used rapidly.

**Stir well before using the product, close tightly the container to preserve the properties.**

Our technical service is at your disposal for any recommendation.